



SUBMERSIBLE LEVEL TRANSMITTER

MODEL BR313L

PRODUCT OVERVIEW:

The Model BR313L from Blue Ribbon Corporation is a line of highly accurate and reliable submersible level transmitters. Their corrosion-resistant 316L stainless steel construction and an integrated hydrophobic breather vent help to provide years of maintenance-free service life.

FEATURES:

- Ranges of 0-20" WC thru 300 PSI (50 MBAR to 21 BAR)
- Rated to 900 FTWC (275 meters WC)
- 0.875" Diameter
- Up to $\pm 0.10\%$ FSO accuracy
- 316L stainless steel housing with optional titanium
- Hytrel jacketed cable with optional Tefzel®
- Lightning suppression as standard

APPLICATIONS:

- Wet wells, ponds, rivers and tank level measurements
- Water treatment
- Ground water monitoring
- Dredging levels
- Shipboard level control

FIELD OPTIONS:

- Slim 0.69" (1.74 cm) diameter (Model BR313S)
- Titanium construction (Model BR313L-NI)
- Additional Hytrel and Tefzel® jacketed cable lengths
- Tapered inlet with stand-off plate for wastewater
- Remote zero and span adjustments



Model BR313L
Submersible Level Transmitter

BR5SL-002
REV-A


SUBMERSIBLE LEVEL TRANSMITTER

DIMENSIONAL DRAWING

All dimensions are in inches (mm)

STANDARD WIRING

WIRE	MODEL 313L
RED	+EXC/SIG
BLK	-EXC/SIG
GRN	N/C
WHT	N/C
SHIELD	OPEN



REFERENCE SPECIFICATIONS

ELECTRICAL	MECHANICAL
• Excitation Voltage: 9 to 36 Vdc • Output Signal: 4-20 mA • Circuit Protection: Short circuit or reversed wired – Indefinite • Load Resistance: 1400 Ω max. at 40 Vdc excitation • Response Time: ≤ 5 ms to 90% • Connection: Hytrel jacketed, 4-conductor, 18 AWG with vent tube and hydrophobic filter, 8' long, other lengths available.	• Zero Balance and FSO: $\pm 1.0\%$ FSO @ +70 °F • Process Connection: PVC bullet nose • External Pressure: Rated to 900 FTWC (274 meters) max. • Proof Pressure: 2X FSO • Burst Pressure: 4X FSO • Approximate Weight: 10 oz (0.3 kg) nominal, options may increase weight • Diameter: 0.875" (2.22 cm)
MATERIALS OF CONSTRUCTION	PRESSURE RANGES
• Housing: 316L stainless steel, optional titanium • Pressure Cavity: 316L stainless steel	• 0-20" WC thru 0 to 300 PSI (0-50 MBAR thru 0-21 BAR)
STATIC ACCURACY (RSS) (HYSTERESIS, NON-LINEARITY & REPEATABILITY @ +70 °F)	THERMAL SPECIFICATIONS
Standard: $\pm 0.5\%$ FSO, $\pm 0.2\%$ FSO, and $\pm 0.1\%$ FSO	• Compensated: 0 °F to +140 °F (-32 °C to +60 °C) • Operating: -40 °F to +185 °F (-40 °C to +85 °C) • Storage: -40 °F to +195 °F (-40 °C to +90.6 °C) • Effect on Zero/Span: $< \pm 2.0\%$ FSO/100 °F

All specifications are for reference purposes only. In the interests of continuous product improvement, all specifications are subject to change without notice. Please contact Blue Ribbon Corporation for assistance with your application.

